

FIG. 1


CLIENT SERVICING
50
REAL-TIME STREAMING ?
NO
YES
51
INPUT NEW MPEG-2 FILE ?
NO
YES
52
INPUT NEW MPEG-2 FILE AND CREATE REDUCED-QUALITY MPEG FILE AS AVAILABLE RESOURCES PERMIT
53
PLAY LIST EDITING ?
NO
YES
54
BROWSE THROUGH REDUCED-QUALITY MPEG FILE TO SELECT IN-POINTS AND OUT-POINTS OF CLIPS TO BE SPLICED
55
NETWORK CONGESTION ?
YES
NO
56
STREAM COMPRESSED VIDEO FROM REDUCED-QUALITY MPEG FILE
57
REDUCED QUALITY REQUESTED ?
YES
NO
58
TRICK MODE REQUESTED ?
YES
NO
59
LOW SPEED-UP ?
YES
NO
60
STREAM ORIGINAL QUALITY I-FRAMES AND 3 FREEZE FRAMES PER I-FRAME
61
SELECT 1 OR 2 FREEZE FRAMES PER I-FRAME FOR DESIRED SPEED-UP
62
STREAM REDUCED-QUALITY I-FRAMES AND INSERTED FREEZE FRAMES
63
STREAM ORIGINAL QUALITY MPEG-2 CODED VIDEO

FIG. 2


MPEG SPLICING
121
INPUT DESIRED END FRAME OF FIRST CLIP AND DESIRED START FRAME OF SECOND CLIP
122
FIND CLOSEST I FRAME PRECEDING DESIRED START FRAME TO BE THE IN-POINT FOR SPLICING
123
ADJUST CONTENT OF THE FIRST CLIP NEAR THE END FRAME OF THE FIRST CLIP AND ADJUST CONTENT OF THE SECOND CLIP NEAR THE IN POINT IN ORDER TO REDUCE PRESENTATION DISCONTINUITY AND PREVENT DECODER BUFFER OVERFLOW WHEN DECODING THE SPLICED MPEG STREAM
124
RE-FORMATTING INCLUDING RE-STAMPING OF PTS, DTS AND PCR'S FOR AUDIO AND VIDEO
END

FIG. 3


SEAMLESS VIDEO SPLICING
141
ANCHOR THE FIRST DTS OF THE SECOND CLIP AT ONE FRAME INTERVAL LATER THAN THE LAST DTS OF THE FIRST CLIP TO PREVENT VIDEO DECODING DISCONTINUITY
DOES THE PCR EXTRAPOLATED TO THE BEGINNING FRAME OF THE SECOND CLIP FALL JUST AFTER THE ENDING TIME OF THE FIRST CLIP ?
142
NO
YES
143
ADJUST THE CONTENT OF THE FIRST CLIP SO THAT THE PCR EXTRAPOLATED TO THE BEGINNING FRAME OF THE SECOND CLIP FALLS JUST AFTER THE ENDING TIME OF THE FIRST CLIP
END

FIG. 4


VIDEO SPLICING
151
DETERMINE THE LAST DTS/PTS OF THE FIRST CLIP (DTS_{L1})
152
DETERMINE THE TIME OF ARRIVAL (T_e) OF THE LAST BYTE OF THE FIRST CLIP
153
ADD ONE FRAME INTERVAL TO DTS_{L1} TO FIND THE DESIRED FIRST DTS LOCATION FOR THE SECOND CLIP ($DTS_{F1} = DTS_{L1} + 1/FR$)
154
KEEPING THE $DTS-PCR_e$ RELATION UNALTERED FOR THE SECOND CLIP, FIND THE TIME INSTANT T_s AT WHICH THE FIRST BYTE OF THE SECOND CLIP SHOULD ARRIVE
($T_{START} = DTS_{F2} - PCR_{e2}$)
($T_S = DTS_{F1} - T_{START}$)
B

FIG. 5


B
IS
$T_S = T_e + \frac{8}{\text{BIT RATE}}$
?
155
NO
YES
IS
$T_S < T_e + \frac{8}{\text{BIT RATE}}$
?
156
NO
YES
157
INSERT NULL TS PACKETS TO COMPENSATE FOR THE GAP BETWEEN T_e AND T_s
$G_r = \frac{(T_s - T_e)(\text{BIT RATE})}{8} - 1$
158
OPEN UP A CERTAIN AMOUNT OF SPACE IN THE FIRST CLIP TO ACHIEVE
$T_s = T_e + \frac{8}{\text{BIT RATE}}$
THE NUMBER OF BYTES TO DROP IS
$1 + \frac{(T_e - T_s)(\text{BIT RATE})}{8}$
IF POSSIBLE, REMOVE NULL PACKETS TO DROP THE BYTES, OTHERWISE, REPLACE ONE OR MORE FRAMES AT THE END OF THE FIRST CLIP WITH CORRESPONDING REDUCED-QUALITY FRAMES.
159
CONCATENATE THE STREAMS
160
COMPUTE THE VIDEO TIME STAMP OFFSET
V_{offset}
END

FIG. 6



FIG. 7



FIG. 8



FIG. 9


TRICK MODE STREAM
181
Input MPEG-2 TS from which a trick mode clip will be extracted.
182
Video elementary stream (VES) extracted.
183
Audio elementary stream (AES) extracted.
184
I frame extraction and valid PES formation.
185
SNR scaling of the I-frames-only PES
186
Freeze P frame insertion and valid PES formation.
187
Selection and concatenation of the appropriate audio access units (from the original asset) based on the structure of the VES in the trick mode clip and valid PES encapsulation around these audio access units.
188
TS stream generation by multiplexing the above video PES into a system info (SI) and audio PES carrying TS skeleton.
END

FIG. 10



FIG. 11
(PRIOR ART)



FIG. 12



FIG. 13



FIG. 14


FDSNR_LM
261
Parse and copy the differential DC coefficient VLC.
262
Parse and decode all (run, level) event VLCs until and including the first EOB marker.
263
Transform the quantization indices to quantized coefficient values.
264
Sort the coefficients in descending order of their magnitudes.
265
keep the first k coefficients of the sorted list and set the last 63-k coefficients of the sorted list to zero.
266
Apply (run, level) event formation and entropy encoding to the new set of coefficients.
267
Copy the resulting VLCs to the output until and including the EOB marker
RETURN

FIG. 15


FIND K MAX VALUES OUT OF N VALUES
271
k < ½n ?
YES
NO
272
k << ½n ?
YES
NO
273
SORT FIRST k AND THEN SCAN LAST n-k FOR ANY GREATER THAN THE MIN OF THE FIRST K, AND IF SO, REMOVE THE MIN OF THE FIRST K AND INSERT THE GREATER VALUE INTO THE SORTED K VALUES.
274
PERFORM k BOTTOM-UP BUBBLE-SORT PASSES OVER THE N VALUES TO PUT K MAX VALUES ON TOP
275
k >> ½n ?
NO
YES
277
PERFORM n-k TOP-DOWN BUBBLE-SORT PASSES OVER THE N VALUES TO PUT n-k MIN VALUES ON THE BOTTOM
276
SORT LAST n-k AND THEN SCAN FIRST k FOR ANY LESS THAN THE MAX OF THE LAST n-k, AND IF SO, REMOVE THE MAX OF THE LAST n-k AND INSERT THE LESSER VALUE INTO THE SORTED n-k VALUES
RETURN

FIG. 16


SORT K FROM N
281
i ← 0
282
GET NEXT COEFFICIENT FROM INPUT STREAM
283
EOB ?
YES
RETURN
NO
284
i < k ?
NO
YES
285
PUT COEFFICIENT INDEX AND MAGNITUDE INTO SORT LIST
286
i ← i+1
287
SORT THE LIST OF K COEFFICIENTS BY MAGNITUDE
C
C
288
COEFF. MAGNITUDE > MAGNITUDE AT END OF LIST?
YES
NO
D
289
GET NEXT COEFFICIENT FROM INPUT STREAM
290
EOB ?
C
NO
YES
RETURN
291
REMOVE ENTRY AT THE END OF THE LIST
292
BINARY SEARCH FOR RANK POSITION OF CURRENT COEFFICIENT
293
INSERT CURRENT COEFFICIENT INDEX AND MAGNITUDE INTO THE LIST AT THE RANK POSITION
C

FIG. 17


HASH TABLE
300
HASH LISTS
301
0
1
2
3
2^M-1
1
0
0
3
2
0
1
0
Cindex
Cindex
Cindex
Cindex
Cindex
Cindex

FIG. 1B


APPROXIMATE SORT K FROM N
311
CLEAR HASH TABLE
312
GET NEXT COEFFICIENT FROM INPUT STREAM
313
EOB ?
YES
NO
314
STRIP HASH TABLE INDEX FROM MSBs OF COEFFICIENT MAGNITUDE
315
INSERT COEFFICIENT INDEX ON HASH LIST OF INDEXED HASH TABLE ENTRY
316
i ← 2^M-1
j ← k
317
INDEX HASH TABLE WITH i
318
ENTRY=0 ?
E
YES
NO
319
i=0 ?
NO
YES
320
i ← i-1
RETURN
321
GET NEXT ENTRY FROM HASH LIST AND PUT COEFFICIENT IN THE OUTPUT STREAM
322
END OF LIST ?
E
YES
NO
323
J ← J-1
324
J≤0 ?
NO
YES
RETURN

FIG. 19


MODIFIED FDSNR_LM
331
FIND UP TO k LARGEST MAGNITUDE NON-ZERO AC DCT COEFFICIENTS (i.e., THE "QUALIFYING COEFFICIENTS") FOR THE BLOCK
332
BEGIN (RUN, LEVEL) CODING OF THE QUALIFYING COEFFICIENTS IN SCAN ORDER, USING THE SECOND CODING TABLE (TABLE 1)
337
CONTINUE (RUN, LEVEL) CODING OF THE QUALIFYING COEFFICIENTS IN SCAN ORDER USING THE SECOND CODING TABLE
333
ESCAPE SEQUENCE ?
YES
NO
334
LEVEL >40 ?
NO
YES
335
IF POSSIBLE, INCLUDE A NON-ZERO, NON-QUALIFYING AC DCT COEFFICIENT IN THE (RUN, LEVEL) CODING TO ELIMINATE THE ESCAPE SEQUENCE
336
END OF BLOCK ?
NO
YES
RETURN

FIG. 20


ATTEMPT ELIMINATION OF ESCAPE SEQUENCE
341
IDENTIFY THE FIRST QUALIFYING COEFFICIENT AND THE SECOND QUALIFYING COEFFICIENT CAUSING THE ESCAPE SEQUENCE
342
LOOK FOR A NON-ZERO, NON-QUALIFYING AC DCT COEFFICIENT BETWEEN THE FIRST AND THE SECOND QUALIFYING COEFFICIENTS IN THE SCAN ORDER SEQUENCE
343
NONE FOUND ?
YES
RETURN UNSUCCESSFUL
NO
344
(RUN, LEVEL) CODE THE NON ZERO NON-QUALIFYING COEFFICIENT
345
ESCAPE SEQUENCE ?
YES
NO
346
(RUN, LEVEL) CODE THE SECOND QUALIFYING COEFFICIENT, USING THE NEW RUN LENGTH
347
ESCAPE SEQUENCE ?
YES
NO
348
CONTINUE SEARCH ?
YES
NO
RETURN SUCCESSFUL
349
SEARCH FOR ADDITIONAL NON-ZERO NON-QUALIFYING COEFFICIENTS THAT WILL ELIMINATE THE ESCAPE SEQUENCE
350
MORE FOUND ?
YES
NO
RETURN SUCCESSFUL
351
SELECT THE NON-QUALIFYING COEFFICIENT GIVING THE SHORTEST OVERALL CODE LENGTH AND/OR THE LARGEST MAGNITUDE FOR THE BEST PSNR
RETURN SUCCESSFUL

FIG. 21



FIG. 22



FIG. 23



FIG. 24



FIG. 25

1 - Play from start 1 sec
2 - Pause
3 - Fast Forward to 29 min
4 - Pause
5 - Play 1 sec
6 - Pause
7 - Fast Reverse to 1 sec
8 - Pause
9 - Play Normal

FIG. 26B



FIG. 26A

	READ	WRITE
Copy of the asset with all the data	EMPEG2	EMPEG2
Copy only the main asset	RAW	MPEG2
Archive	EMPEG2	EMPEG2
Play	MPEG2	
Record		MPEG2

FIG. 27



FIG. 28


MPEG-2 AUDIO-VISUAL TRANSPORT STREAM
411
SELECTIVE ELIMINATION OF NON-ZERO AC DCT COEFFICIENTS TO SLIGHTLY REDUCE THE AVERAGE BIT RATE
414
BIT RATE MONITOR
416
NO. BITS REMOVED
423
REMOVE OR NOT REMOVE ONE NON-ZERO AC DCT COEFFICIENT PER 8X8 BLOCK
422
424
NO. BITS TO BE REMOVED PER COMPUTATION INTERVAL
MULTIPLEXED MPEG-2 TRANSPORT STREAM
TRANSPORT STREAM MULTIPLEXER
413
415
418
DESIRED BIT RATE FOR MULTIPLEXED MPEG-2 TRANSPORT STREAM
420
COMPUTATION OF DESIRED BIT RATE CHANGE IN MPEG-2 AUDIO VISUAL TRANSPORT STREAM
421
419
BIT RATE OF MULTIPLEXER OVERHEAD
BIT RATE MONITOR
417
MPEG-2 CLOSED-CAPTIONING TRANSPORT STREAM
412

FIG. 29


Original encoded frame bits allocation/Block
501
502
509
510
Reduced frame bits allocation/Block
503
504
505
506
507
508

FIG. 30



FIG. 31


x 10^5
14
12
10
8
6
4
2
0
0
10
20
30
40
50
60
70
I frame size [bits]
I frame number
531
532
533
534

FIG. 32


ADAPTIVE BIT RATE REDUCTION
541
CLEAR BUCKET
BUK←0
542
PARSE VIDEO FRAME TO 8x8 DCT BLOCKS
543
DETERMINE DCT COEFFICIENT BIT RATE REDUCTION FACTOR (RF)
544
GET FIRST BLOCK (J←0)
545
PARSE THE BLOCK
546
NON-ZERO AC DCT COEFFICIENTS ?
NO
YES
J
L
547
END OF FRAME ?
NO
YES
549
END OF CLIP?
YES
NO
550
GET NEXT FRAME
END
548
GET NEXT BLOCK (J←J+1)

FIG. 33



FIG. 34


K
571
NBC ≤ NBA ?
NO
YES
572
PUT THE REMAINING UNALLOCATED BITS INTO THE BUCKET
BUK ← BUK + NBA
L
573
TRANSFER THE COEFFICIENT TO THE REDUCED-RATE MPEG DATA
574
DECREMENT THE NUMBER OF BITS AVAILABLE (NBA) FOR ENCODING BY THE NUMBER OF BITS FOR ENCODING COEFFICIENT (NBC)
NBA ← NBA - NBC
575
MORE NON-ZERO AC DCT COEFFICIENTS ?
NO
YES
M

FIG. 35


DETERMINE THE COEFFICIENT BIT RATE REDUCTION FACTOR (RF) FOR A REDUCTION FROM AN MPEG SOURCE HAVING A KNOWN CONSTANT BIT RATE
581
DETERMINE THE OFFSET RATE (S) OF BITS IN THE ORIGINAL-QUALITY MPEG SOURCE THAT ARE NOT BITS OF THE AC DCT COEFFICIENTS
582
COMPUTE THE COEFFICIENT BIT RATE REDUCTION FACTOR (RF) FROM THE KNOWN CONSTANT BIT RATE (BO) AND PADDING (PD) OF THE ORIGINAL-QUALITY MPEG SOURCE, THE OFFSET RATE (S), AND THE DESIRED REDUCED RATE (BR) OF THE REDUCED-QUALITY MPEG DATA
$RF = \frac{BR-S}{BO-PD-S}$
RETURN

FIG. 36


DETERMINE THE COEFFICIENT BIT RATE REDUCTION FACTOR (RF) FOR A REDUCTION FROM AN MPEG SOURCE HAVING AN UNKNOWN OR VARIABLE BIT RATE
591
DETERMINE VIDEO FRAME SIZE IN BITS (VS)
592
DETERMINE A MOVING AVERAGE VIDEO FRAME SIZE OVER THE LAST N FRAMES (VAVS)
593
CALCULATE A TARGET AVERAGE VIDEO FRAME SIZE (VRAVS) FROM AN ACCURACY RATE CONTROL FACTOR (AR), THE DESIRED REDUCED RATE (BR) OF THE REDUCED-QUALITY MPEG DATA, AND THE VIDEO FRAME RATE (FR)
VRAVS = AR * BR/FR
594
DETERMINE NO. OF BITS (BS) IN THE FRAME THAT ARE NOT BITS OF THE AC DCT COEFFICIENTS
595
COMPUTE THE COEFFICIENT BIT RATE REDUCTION FACTOR (RF)
RF = VRAVS/VAVS
RETURN

FIG. 37


605
ORIGINAL-QUALITY MPEG-2 CODED VIDEO
603
REAL-TIME ADAPTIVE BIT RATE REDUCTION BY SELECTIVE ELIMINATION OF NON-ZERO AC DCT COEFFICIENTS
REDUCED-QUALITY MPEG-2 STREAM
604
601
602
INC
DEC
BUCKET (BUK)
VBV<TH1
VBV>TH2
VIDEO BUFFER MODEL

FIG. 38